

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
3 March 2005 (03.03.2005)

PCT

(10) International Publication Number
WO 2005/020449 A3

(51) International Patent Classification⁷: **H04B 5/00**,
G01S 11/06

New Road, Great Baddow, Chelmsford, Essex CM2 7QT
(GB).

(21) International Application Number:
PCT/GB2004/003566

(74) Agents: MCCANN, Heather et al.; Electronic Intellectual
Property, Suite 308, The Foundry, 156 Blackfriars Road,
London SE1 8EN (GB).

(22) International Filing Date: 19 August 2004 (19.08.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0319518.7 19 August 2003 (19.08.2003) GB

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(71) Applicant (*for all designated States except US*): PLEX-
TEK LIMITED [GB/GB]; London Road, Great Chester-
ford, Essex CB10 1NY (GB).


(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): RICHARDS, Tony
[GB/GB]; Plectex Limited, London Road, Great Chester-
ford, Essex CB10 1NY (GB). FITZ, Steve [GB/GB]; 16

[Continued on next page]

(54) Title: PROXIMITY DETECTING APPARATUS



(57) Abstract: Arrangements according to the invention embody a radio frequency receiver for use in a proximity detecting system, the radio frequency receiver comprising at least one antenna coil operable to receive radio frequency signals; tunable receiver circuitry arranged in operative association with the antenna coil and being arranged to modify the frequency at which radio signals are received by the radio frequency receiver; and a signal processor arranged to amplify and filter signals received by the radio frequency receiver, wherein the radio frequency receiver is operable to receive and process radio signals of frequencies between 100kHz and 10MHz. By operating in the low frequency range, multi-path problems associated with high frequency equipment (such as reflections from objects located between the path of the transmitter and receiver) are significantly reduced, whilst distance between transmitter and receiver can be identified extremely accurately.



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

(88) Date of publication of the international search report:

21 April 2005